Product Brief

Intel® PRO/1000 PT Quad Port LP Server Adapter

Network Connectivity



Intel® PRO/1000 PT Quad Port LP Server Adapter

Low-Profile Quad Port Copper Gigabit Ethernet Server Adapter for PCI* Express Slots

- Four high-performance PCI Express* 10/100/1000 Mbps connections for slot-constrained servers requiring high bandwidth
- Multi-Gigabit Ethernet Scalability enhances and increases uptime through advanced server features
- Built on Intel® lead-free1 technology



Conserve valuable PCI Express (PCle*) server slots while adding multi-port Gigabit Ethernet capability with the Intel® PRO/1000 PT Quad Port LP Server Adapter. The dedicated input/output (I/O) bandwidth of PCle ensures priority performance on each port – without bus sharing – for Gigabit Ethernet connectivity in Category-5 networks. The Intel PRO/1000 PT Quad Port LP



Server Adapter improves performance in multi-processor systems by balancing network loads across multiple central processing units (CPUs). Additionally, the Intel PRO/1000 PT Quad Port LP Server Adapter supports Intel® I/O Acceleration Technology (Intel® I/OAT)² for faster I/O processing on the new Quad-Core and Dual-Core Intel® Xeon® processor-based servers.

Features	Benefits		
Two Intel® 82571GB Gigabit Controllers	Enables four Gigabit Ethernet connections on a single adapter, delivering increased bandwidth for slot-constrained servers and providing high performance, reliability, and low-power use in two single, integrated, dual port PCI Express Gigabit Ethernet controller chips		
Low-profile	Enables higher bandwidth and throughput from standard and low-profile PCle slots and servers		
Load balancing on multiple CPUs	Increases performance on multi-processor systems by efficiently balancing network loads across CPU cores when used with Receive-Side Scaling from Microsoft or Scalable I/O on Linux*		
Intel® I/OAT ²	Accelerates I/O with higher throughput and lower CPU utilization by offloading processing overhead		
Virtualization	Multi-port cards provide the platform with the port density required for virtualized environments		
Interrupt moderation	Delivers increased performance while significantly reducing CPU utilization		
Compatible with x4, x8, and x16 standard and low-profile PCI Express* slots	Allows quad-port operation in almost any PCI Express server slot, except x1 slots, and allows each port to operate without interfering with the other		
Support for most network operating systems (NOS)	Enables widespread deployment		
Remote management support	Reduces support costs with remote management based on industry-wide standards		
Category-5 unshielded twisted pair (UTP), 4-pair cabling	Uses existing 4-pair cabling and saves re-wiring costs		
RoHS compliant ³ , lead-free ¹ technology	Compliant with the European Union directive (effective as of July 2006) to reduce the use of hazardous materials		
Intel® PROSet Utility for Windows*	Provides point-and-click power over individual adapters, advanced adapter features, connection teaming, and Device Managvirtual local area network (VLAN) configuration		
Advanced cable diagnostics	Dynamically tests and reports network problems (error rate, cable length) and automatically compensates for cable issues (cross-over cable, wrong pin-out/polarity)		
Intel backing	Backed by an Intel® limited lifetime warranty, 90-day money-back guarantee (U.S. and Canada), and worldwide support		

The Intel PRO/1000 PT Quad Port LP Server Adapter's low-profile design, the industry's first server adapter to incorporate four Gigabit Ethernet connections in a low-profile PCI Express slot, improves server throughput and rack density at the same time.

The Intel PRO/1000 PT Quad Port LP Server Adapter represents the sixth generation of Intel® network adapters for Gigabit Ethernet, and features 10/100/1000 Mbps self-configuration

for compatibility with mixed-speed network infrastructure. For easy installation and management, all Intel® PRO Network Connections are supported by Intel® PRO Intelligent Install and the new Intel® PROSet Utility for Windows* Device Manager. Intel PROSet simplifies adapter installation and gives you point-and-click power to configure and manage all your Intel PRO Network Connections for connectivity you can count on.

Specifications

90-day, money-back guarantee (U.S. and Canada)

General		Advanced Software Features	
Product code	EXPI9404PTL ⁴	Adapter fault tolerance (AFT)	•
Connectors	Four RJ-45	Switch fault tolerance (SFT)	•
EEE standards/network topology	10BASE-T, 100BASE-TX, 1000BASE-T	Adaptive load balancing (ALB)	•
		Fast EtherChannel*5 (FEC)	•
Wiring	Category-5, unshielded twisted pair (UTP), 4-pair	Gigabit EtherChannel*5 (GEC)	
		Teaming support	Scales up to 8 connections
Adapter Product Features		Multiple teams	Supports 4 separate teams,
Intel® PROSet Utility and Intel® PRO			maximum
Intelligent Install for easy installation		IEEE 802.3ad* (link aggregation control protocol)⁵	•
Intel® lead-free¹ technology	•	Test switch configuration	Tested with major switch original
Plug and play specification support	Standard		equipment manufacturers (OEMs)
Auto-negotiation, full-duplex capable	•	PCle Hot Plug*/Active peripheral	•
Intel® I/OAT²	•	component interconnect (PCI)	
Integrated media access control (MAC)	•	EEE 802.1Q* VLANs	•
and physical layer (PHY)		EEE 802.3* (z, ab, u, x) flow control support	•
Includes a full-height bracket RoHs³	-	TCP checksum offload – transmission	
	100 :- C-+ 100/1000	control protocol (TCP), user datagram	
Cable distance	100 m in Category-5 for 100/1000 Mbps; and Category-3 for 10 Mbps	protocol (UDP), Internet protocol (IP)	
	1, 3, 1	IEEE 802.1p*	•
Network Management		TCP segmentation/large send offload	•
Wired for Management (WfM) baseline v2.0 enabled for servers	•	Interrupt moderation	•
DMI 2.0 support, Windows Management	•	Technical Features	
Instrumentation (WMI) and SNMP-manageable SMBus support		Data rate(s) supported per port	10, 100, and 1000 Mbps
Remote Installation Services (RIS)		Bus type	PCI Express 1.0a
Diagnostics (loopback, testability, PHY register access)	•	Bus width	x4 lane PCI Express, operable in x4, x8, x16 slots
Advanced configuration and power interface (ACPI) 1.0 power management		Bus speed (x4, encoded rate)	10 Gbps uni-directional; 20 Gbps bi-directional
(EEPROM-SPI and single EEPROM support	•
Wake on LAN* support over PCI Express* PXE 2.0 enabled through boot read-only memory (ROM)	•	Interrupt levels	INTA, INTB, INTC, INTD
		IEEE support	802.3ab*
		Hardware certifications	FCC B, UL, CE, VCCI, BSMI, CTICK, MI
Network Operating Systems (NOS) Software Support	Controller-processor	Intel® 82571GB
Microsoft Windows* Server 2003, Enterprise, Datacenter (32- and 64-bit)	•	Typical power consumption	12.096 W (12 V @ 1.008 A)
Microsoft Windows 2000		Operating temperature	0-55° C
Red Hat Linux* 2.4x or later (32- and 64-bit)		LEDs	4 (1/port, link and speed) solid
FreeBSD 4.x or later			and blinking
Novell Netware*		Physical Dimensions	
Sun Solaris* x86, OS 8 and later			16.77 (6.601:-)
SCO Open Server 5, OpenUNIX 8*		Length	16.77 cm (6.601 in)
aco open servera, openonia 8"	-	Width	6.89 cm (2.713 in)
Intel Backing		Height of end bracket	8.00 cm (3.153 in)
Limited lifetime warranty	_	•	

Order Code

Single Unit: EXPI9404PTL⁴
Bulk Pack: EXPI9404PTLBLK (order 5, get 5)

Companion Products

Consider these Intel® products in your server and network planning:

- Intel® PRO/1000 Server Adapters
 - Copper or fiber-optic network connectivity, up to four ports per card
 - Solutions for PCI Express, PCI-X*, and PCI interfaces
- Intel® PRO/10GbE Server Adapters
 - CX4 offering for cost-effective 10 Gigabit-over-copper connections
 - Short-range and long-range connectivity solutions for fiber-optic cabling
- Intel® PRO/1000 Desktop Adapters for PCI Express and PCI interfaces
- Other Intel® PRO Desktop and Server Adapters
- Intel® Xeon® processors
- Intel® Server Boards

Network-Ready PCs

Top PC and server manufacturers offer Intel® adapters in their new products. Specify or ask for Intel PRO Network Connections with your next PC, server, or mobile PC purchase. For a list of preferred suppliers, visit us at: www.intel.com/network/connectivity/how_to_buy/index.htm.

Customer Support

Intel® Customer Support Services offers a broad selection of programs including phone support and warranty service. For more information, contact us at http://support.intel.com/support/network. Service and availability may vary by country.

For Product Information

To speak to a customer service representative regarding Intel products, please call 1-800-538-3373 (U.S. and Canada) or visit http://www.intel.com/support/9089.htm for the telephone number in your area. For additional product information on Intel® Networking Connectivity products, visit http://www.intel.com/network/connectivity.

To see the full line of Intel Network Adapters for PCI Express, visit www.intel.com/network/connectivity

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH INTEL® PRODUCTS. EXCEPT AS PROVIDED IN INTEL'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, INTEL ASSUMES NO LIABILITY WHATSOEVER, AND INTEL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY RELATING TO SALE AND/OR USE OF INTEL PRODUCTS, INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT, OR OTHER INTELLECTUAL PROPERTY RIGHT. INTEL MAY MAKE CHANGES TO SPECIFICATIONS, PRODUCT DESCRIPTIONS, AND PLANS AT ANY TIME, WITHOUT NOTICE.

Copyright © 2008 Intel Corporation. All rights reserved.

Intel, the Intel logo, Intel. Leap ahead., Intel. Leap ahead. logo, and Xeon are trademarks of Intel Corporation in the U.S. and other countries.

*Other names and brands may be claimed as the property of others.

Please Recycle

315880-004US (intel

Lead has not been intentionally added, but lead may still exist as an impurity below 1000 ppm, or an approved RoHS exemption applies.

²Intel® I/O Acceleration Technology (Intel® I/OAT) requires an operating system that supports Intel I/OAT.

³ Lead and other materials banned in RoHS Directive are either (1) below all applicable substance thresholds as proposed by the EU or (2) an approved/pending exemption applies.

⁴Bulk packs also available for minimum order quantities of five adapters. One driver CD per order of five units.

⁵ Available only when used with a capable switch.